

## 880.214 – Gantry level luffing slewing crane

<b>Manufacturer:</b>	
<b>Year of construction:</b>	
<b>Lifting capacity</b>	<b>Outreach</b>
12,5 to.	von 7,0 bis 26,0 m
20,0 to.	von 7,0 bis 18,5 m
25 to.	von 7,0 bis 15,5 m
<b>Speed and Capacity</b>	
<b>Hoisting speed</b>	25,0 t, 14 m/min 1 x 80 kW
	18,0 t 25 m/min
	8,5 t 45 m/min
	4,0 t 90 m/min
<b>Slewing gear</b>	1,6 U/min 2x 8,5 kW
<b>Level luffing gear</b>	30 s 1x 37 kW
<b>Travelling gear</b>	30 m/min 4x 6,3kW
<b>Power supply</b>	appr- 170 kW
<b>Voltage/ Frequency</b>	380 V/ 50 Hz
<b>Using temperature</b>	+40,0 bis -25°C
<b>Crane rail</b> S49	Kopfbreite 65 mm
<b>Weight total appr.</b>	140 to.
<b>Load suspension device</b>	single hook
<b>Hight of lift</b>	- 9 m bis + 22 m
<b>Span width</b>	6.0 m
<b>Location:</b>	<b>Dismantled and stored</b>

